

GO xPress Line

GO xPress 5 Way Heat Press

USP (Unique Selling Proposition)

The GO xPress 5 Way is a convenient set of five different sized high performance bottom working plates allowing for a variety of materials to be sublimated on with ease. The ideal dye sublimation set for apparel applications.

Key Features

- Industrial strength five piece interchangeable plate-set for printing on apparel
- Heating boards come in five convenient sizes including: 40 x 50 cm (15.75" x 19.7"), 35 x 30 cm (13.7" x 11.8?"), 13 x 13 cm (5.1" x 5.1"), 38 x 18 cm (15" x 7.08"), 12 x 45 cm (4.7" x (17.71")
- Power: 1400 W (1.4 KW)
- Voltage: 110 V
- Amps: 13 A
- Temperature range: 0-399 with real time display of temperature
- Time control: 0-999 sec
- Printing area: 40 x 50cm (16" x 20")
- Centrally located pressure adjustment for consistently even pressure
- Wide opening for convenience, ease and efficiency



GO xPress 3041

USP (Unique Selling Proposition)

The GO xPress 3041 is a high performance heat press system for transferring high quality images onto a variety of substrates with ease. The GO xPress 3041's automatic release of the upper board when time is up makes for the perfect press every time.

Key Features

- High performance industrial strength heat press for apparel
- Quick heating time with energy saver consumption-Saves time and money
- Cost effective with unsurpassed value
- Drawer type working table with easy to use functions
- Heating board heats up evenly with integrated tube technology
- Centrally located pressure adjustment for consistently even pressure
- Wide opening for convenience, ease and efficiency
- Printing area: 31" x 41" (75 x105cm)
- Voltage: 220 V
- Power: 9 KW
- Amp: 14 A
- Temperature range: 0 - 399° C
- Time range: 0-999 sec; Top automatically opens when timer is complete
- Actual weight: 97 Kg



The technical specifications and performance capabilities listed herein are subject to change at any time and may not reflect actual production capabilities. Graphics One is not responsible for any incorrect information contained herein and urges any buyer or potential buyer to test the product prior to making a purchase.

Graphics One, LLC 3300 San Fernando Blvd #101, Burbank, CA 91504, USA Tel: 818-260-9591, Fax: 818-260-9589, Email: info@graphicsone.com, Website: www.graphicsone.com © Copyright 2000-2008 Graphics One, LLC GO (Graphics One), GO Atomic, GO elnk, GO glnk, GO hlnk, GO plnk, GO xlnk, GO dMax 4, GO GEO, GO Vivalnk, GO MegaBanner, GO Billboard, GO yPlay, GO uFill, GO ezFill, GO EcoOne, GO Fizzion, GO Sublimator are trademarks of Graphics One, LLC. All other trademarks are properties of their respective companies.

PRODUCT INFO

GO xPress Line

PRODUCT INFO

GO xPress 4048 Dual

USP (Unique Selling Proposition)

The GO xPress 4048 Dual is a high performance heat press system with double the working space for transferring high quality images onto a variety of substrates with ease.

Key Features

- High performance industrial strength heat press with double the working space of a normal heat press
- Quick heating time with energy saver consumption-saves time and money
- Cost effective, unsurpassed value
- Drawer type working table with easy to use functions
- Heating board heats up evenly with integrated tube technology
- Centrally located pressure adjustment for consistency
- Wide opening for convenience, ease and efficiency
- Printing area: 100 x 120cm
- Voltage: 220 V
- Power: 12 KW
- Amp: 18 A
- Temperature range: 0 - 399° C
- Time range: 0-999 sec



GO xPress 1620

USP (Unique Selling Proposition)

The GO xPress 1620 is a high performance heat press system with pull out heating board and automatic timer for your convenience.

Key Features

- High performance industrial strength heat press -lower heating board can be pulled out for your convenience
- Quick heating time with energy saver-Saves time and money
- Cost effective with unsurpassed value
- Pull out working table with easy to use functions
- Vertical pressure allow printing thicker materials
- Heating board heats up evenly with integrated tube technology
- Printing area: 40 x 50cm (16"x20")
- Voltage: 110 V
- Power: 1,400 W (1.4 KW)
- Amps: 13 A
- Temperature range: 0 - 399° C; real time display of temperature
- Time range: 0-999 sec; Automatic timer



The technical specifications and performance capabilities listed herein are subject to change at any time and may not reflect actual production capabilities. Graphics One is not responsible for any incorrect information contained herein and urges any buyer or potential buyer to test the product prior to making a purchase.

Graphics One, LLC 3300 San Fernando Blvd #101, Burbank, CA 91504, USA Tel: 818-260-9591, Fax: 818-260-9589, Email: info@graphicsone.com, Website: www.graphicsone.com © Copyright 2000-2008 Graphics One, LLC GO (Graphics One), GO Atomic, GO elnk, GO glnk, GO hlnk, GO plnk, GO xlnk, GO dMax 4, GO GEO, GO Vivalnk, GO MegaBanner, GO BillBoard, GO yPlay, GO uFill, GO ezFill, GO EcoOne, GO Fizzion, GO Sublimator are trademarks of Graphics One, LLC. All other trademarks are properties of their respective companies.