


FLUORESCENT EXPOSURE UNITS

E-100

2 Sizes Available



E100-2128-LB



E100-2128



One touch angled control panel (E-200 and E-100)

E-1000

2 Sizes Available



E1-5236



New LCD touchscreen makes it easier to set and save up to 10 preset exposure times. (E-2000 and E-1000)

CE CERTIFIED
BY CERTIFICATION EXPERTS
THE NETHERLANDS

	E-100 Series			E-1000 Series	
	E100-2128-LB	E100-2128	E100-2331	E1-2536	E1-5236
Screen Size (Max OD)	21" x 28" (53 x 71 cm)	21" x 28" (53 x 71 cm)	23" x 31" (58 x 78 cm)	25" x 36" (63 x 91 cm)	52" x 36" (132 x 91 cm)
Image Area	15" x 18" (38 x 46 cm)	15" x 18" (38 x 46 cm)	16" x 33" (40 x 83 cm)	18" x 27" (45 x 68 cm)	47" x 27" (119 x 68 cm)
Bulbs	(4) 20 watt black UV	(4) 20 watt black UV	(6) 40 watt black UV	(6) 47 watt black UV	(14) 47 watt black UV
Compression Type	Pressure pad	Lid with Vacuum Pump	Lid with Vacuum Pump	Lid with Vacuum Pump	Lid with Vacuum Pump
Controls	One Touch Operation	One Touch Operation	One Touch Operation	LCD Touchscreen	LCD Touchscreen

Features

- POWERFUL** Powered vacuum hold down contours rubber blanket to screen for excellent screen to film contact (excludes E-100-LB)
- SMART** Vacuum draws through bottom manifold, no holes in rubber blanket (excludes E-100-LB)
- CONSISTENT** Electronic ballasts for quick starts & steady UV output
- ACCURATE** Timer controls lights & vacuum precisely
- BRIGHT** Unfiltered UV fluorescent bulbs
- COVENIENT** Angled control panel w/ one touch operation
- GUARANTEED** 3 year warranty on manufacturer's defects*
- DEPENDABLE** .25" (.63 cm) thick tempered glass, virtually eliminates breakage

Options

- 120V or 240V
- S-100 stand with wheels (E-100 only)
- Dri-Cab with air circulation (E-100 only)
- Dri-Vault with heated air
- Locking Casters (E-1000 only)

* Excludes rubber blanket



Exposing Units

Technical Specifications



	E200-2128 (LED) E100-2128 (Fluorescent)	E200-2331 (LED) E100-2331 (Fluorescent)	E2-2536 (LED) E1-2536 (Fluorescent)	E2-5236 (LED) E1-5236 (Fluorescent)
Overall Warranty	3 Year	3 Year	3 Year	3 Year
Maximum Screen Size	21" x 28" (53 x 71 cm)	23" x 31" (58 x 78 cm)	25" x 36" (63 x 91 cm)	52" x 36" (132 x 91 cm) or (2) 25" x 36" (63 x 91 cm)
Image Area	15" x 18" (38 x 45 cm)	16" x 33" (58 x 83 cm)	E2 - 24" x 36" (61 x 91 cm) E1 - 18" x 27" (45 x 68 cm)	E2 - 46" x 36" (116 x 91 cm) E1 - 47" x 27" (119 x 68 cm)
Bulbs (LED)	Qty. (3) 18" (61 cm) LED light bars	Qty. (3) 30" (76 cm) LED light bars	Qty. (6) 30" (76 cm) LED light bars	Qty. (12) 30" (76 cm) LED light bars
Bulbs (Fluorescent)	Qty. (4) 20 watt T12-BL, black UV	Qty. (6) 40 watt F28T12 BLHO, Black UV fluorescent 28" (71cm) long	Qty. (6) 47 watt F7761T2 BLC, Black UV fluorescent 30.5" (78cm) long	Qty. (14) 47 watt F7761T2 BLC, Black UV fluorescent 30.5" (78cm) long
Vacuum Pump, Oil-less Diaphragm	1/16 HP 24 hg Max	1/16 HP 24 hg Max	1/4 HP High Output 23 Hg Max	1/4 HP High Output 23 Hg Max
Power & Plug Spec International Available	120V 3.5A NEMA 5-15P plug 240V 2A NEMA 6-15P plug	120V / 60 HZ / 3.5A NEMA 5-15P 240V / 50/60 HZ / 2A NEMA 6-15P	120V / 60 HZ / 3.5A (E2-2536) 120V / 60 HZ / 3.5A (E1-2536) NEMA 5-15P 240V / 50/60 HZ / 2A NEMA 6-15P	120V / 60 HZ / 6.5A (E2-5236) 120V / 60 HZ / 8A (E1-5236) NEMA 5-15P 240V / 50/60 HZ / 4A NEMA 6-15P
Overall Depth x Width x Height	Lid Closed 35.75" x 34.75" x 14" (83 x 88 x 36 cm) Lid Open 35.75" x 34.75" x 28" (83 x 88 x 71 cm)	Lid Closed 41.6 x 36.2 x 17" (105.7 x 92 x 44 cm) Lid Open 41.6 x 36.2 x 32" (105.7 x 92 x 82 cm)	Lid Closed 38.3" x 49.3" x 44.5" (97.3 x 125.3 x 113.1 cm) Lid Open 38.3" x 49.3" x 73.7" (97.3 x 125.3 x 187.3 cm)	Lid Closed 65.3" x 49.3" x 44.5" (165.8 x 125.3 x 113.1 cm) Lid Open 65.3" x 49.3" x 73.7" (165.8 x 125.3 x 187.3 cm)
Overall Weight - Uncrated	100 lbs (45.4 kg)	180 lbs (81.6 kg)	Call for details	Call for details
Shipping Weight*	223 lbs (101 kg) w/ Utility Cart (UC-1000) 483 lbs (219 kg)	386 lbs (175 kg) w/ drying cabinet VDC253610 570 lbs (259 kg)	Call for details	Call for details
Shipping Dimensions*	43" x 43" x 17" (109 x 109 x 43 cm) w/ Utility Cart (UC-1000) 43" x 43" x 35" (109 x 109 x 89 cm)	48" x 45" x 20" (122 x 114.3 x 51 cm) w/ drying cabinet VDC253610 49" x 45" x 38" (124 x 114 x 97 cm)	Call for details	Call for details

Drying Cabinets

Technical Specifications



	Dri-Cab	Dri-Vault - Drying Cabinets		
	VDC-2331	VDC-253610	VDC-2536-24	VDC-513610
Defect Warranty	3 Year	3 Year	3 Year	3 Year
Maximum # of Screens	10 @ maximum size	10 @ maximum size	24 @ maximum size	(10) @ 51" x 36" / (20) @ 25" x 36"
Maximum Screen Size	23" x 31" x 1.625" (58.4 x 78.7 x 4.12 cm)	25" x 36" x 1.625" (63.5 x 91.4 x 4.12 cm)	25" x 36" x 1.625" (63.5 x 91.4 x 5.7 cm)	(10 screens) @ 51" x 36" (20 screens) @ 25" x 36"
Smallest Screen Width	16" (46 cm)	18" (46 cm)	18" (46 cm)	No minimum due to adjustable center tree
Blower (Free Air)	113 CFM (3.2 CMM)	177 CFM (5 cmm) <u>120v</u> or 290 CFM (8.2cmm) <u>240volt</u>	580 CFM (16.4 CMM)	290 CFM (8.2 CMM)
Overall Depth x Width x Height	36" x 26" x 32" (91 x 66 x 81 cm)	39.5" x 34.75" x 32"	39.5" x 34.75" x 81"	37.9" x 62.5" x 32.3"
Heater Wattage	N/A	1,250 Watts 120 Volts or 1,550 Watts 240 Volts	3,100 Watts 240 Volts	1,550 Watts @ 240 Volts
Power & Plug Spec International Available	120V / 1A / 1 Ph. / 60 HZ / NEMA 5-15P plug or 240V / 1A / 1 Ph. / 50/60 HZ / NEMA 6-15P plug	120V / 10A / 1 Ph. / 60 HZ / NEMA 5-15P plug or 240V / 6A / 1 Ph. / 50/60 HZ / NEMA 6-15P plug	240V / 16A / 1 Ph. / 50/60 HZ / NEMA 6-20P plug	240V / 6A / 1 Ph. / 50/60 HZ / NEMA 6-15P plug
Shipping Weight (Assembled)*	212 lbs (55.3 kg)	367 lbs (166.5 kg)	670 lbs (303 kg)	573 lbs (277 kg)
Shipping Dimensions (Assembled)*	43" x 35" x 40" (110 x 89 x 102 cm)	43" x 43" x 48" (109 x 109 x 122 cm)	43" x 43" x 84" (109 x 109 x 213 cm)	69" x 48" x 48" (175.3 x 122 x 122 cm)
Shipping Weight (Unassembled)*	Box # 1 - 121 lbs (55 kg) Box # 2 - 15 lbs (6.8 kg)	N/A	N/A	N/A
Shipping Dimensions (Unassembled)*	Box # 1 - 43" x 29" x 9" (110 x 74 x 23 cm) Box # 2 - 34" x 29" x 8" (87 x 74 x 21 cm)	N/A	N/A	N/A

*All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications. Ex-works from Allentown PA.

1 in = 2.54 cm
1 lb = 0.454 kg