

PRODUCTION INFRARED DRYERS

ECONORed II SERIES

**15 YEAR
HEATER WARRANTY**



- Digital belt speed display for more accurate control
- Focused exhaust system to remove fumes/moisture within chamber
- Excellent air flow to cool the skin of the dryer
- Cures plastisol, water-based and discharge inks!



	30" Belt Version		54" Belt Version	
	EC-II-30	EC-II-30-2	EC-II-54	EC-II-54-2
Standard Wattage	7,200w	14,400w	14,400w	28,800w
Belt Width x Length	30" x 7¼' (76.2 x 220cm)	30" x 10¼' (76.2 x 312cm)	54" x 7¼' (137 x 220cm)	54" x 10¼' (137 x 312cm)
Chamber (tunnel) Length	3' (91.4cm)	6' (183cm)	3' (91.4cm)	6' (183cm)
Cure times: Plastisol***	300+/hr	600+/hr	600+/hr	1,200+/hr
Water Based/Discharge**	100+/hr	200+/hr	200+/hr	400+/hr

Features

- HEAVY DUTY** "X-Series" Conveyor Belt Tracking System
- PRECISE** Infrared Focusing System provides more power for less \$\$
- ADJUSTABLE** 2" - 7" (5 - 17.7 cm) belt-to-heater height adjustment
- ACCURATE** Digital PID Temperature controller is accurate to +/-1° F
- CONSISTENT** Heavy duty DC belt speed motor with digital voltage display
- INNOVATIVE** Engineered to be shorter and smaller with high heat and production.
- EXPANDABLE** Add heat chambers and belt extensions. (HD Drive required over 17' long)

Options

- Add heat chambers @ 3' (.91m) long
- Belt extensions front or rear, 18" (46 cm) increments
- 3 Phase & 208, 380, 480 voltages available
- Exhaust Hood, provides extra fume extraction
- Hat support rail
- Locking casters for easy mobility
- Reversing belt / HD Drive

* Production speeds are estimates and will vary depending on ink manufacturer, humidity of shop, and other variables.



EC-II_0415