



DFR

Direct to Film Remover

AlbaChem® **DFR Direct to Film Remover** removes DTF graphics from all types of fabrics. A strong solvent blend attacks DTF binder allowing the graphic image to be peeled or scraped away.

- Removes DTF Graphics from all Textiles
- Low Odor
- Water Soluble

DIRECTIONS: Unscrew spout cap. Puncture center of white plastic seal. Replace spout cap. Twist to open and close. Follow directions to remove print using DFR.

1. Apply DFR to the fabric underside directly beneath the print area you want to remove. Wait approximately 1 to 5 minutes to allow DFR to penetrate. For best results, after applying DFR let rest for at least 3 minutes. Removing DTF will remove easier with less residue
2. Remove the Print: Gently peel or scrape off the print material. If necessary, drip DFR directly on top of the print, then peel or scrape remaining image.
3. Clean Remaining Residue: Apply additional DFR to a clean, textured cloth (e.g. terry cloth), and wipe away any remaining residue.
4. Rinse and Dry: Rinse the area thoroughly with water to flush out any remaining DFR, run through a washing machine. Blot away excess moisture and allow the fabric to dry. For quicker results, heat press the area to speed up the drying process.
5. Reprint. Once the fabric is completely dry, the area is ready for reprinting.

Packaging:

Item No.	Package Size	Case Pack	Case Weight	Hazmat Information
2020	20 fl. oz. (591 ml)	12	20.5 lbs.	Non-Hazardous

Technical Data

Physical Properties:
Appearance: Clear colorless liquid
Solubility in Water: Yes
Odor: Mild solvent

Environmental:

Volatile Organic Compound (VOC): 50%
Hazardous Air Pollutant (HAP): No
Ozone Depleting Substance: No
SARA 313 Chemicals: No

Consult safety data sheet for all safety and handling information.



Albatross USA Inc.

36-41 36th Street, P.O. Box 6446 • Long Island City, New York 11106
Tel: 718-392-6272 / 800-233-4468 • Fax: 718-392-2899

www.albachem.com

sales@albachem.com