## SILKJET SC4 / UC5 / WP5



## Ink Jet Media for Screen Printing

**Product Description** 4 or 5-mil Clear Polyester Film, Ink jet Printable

**Application** Film Positives to burn silk screens

Short Roll Sizes
No Interleaf Paper

16.5 in., 24 in., 36 in., 42 in. x 100 ft.

Sheet Sizes
With Interleaf Paper

8.5 in. x 11 in., 8.5 in. x 14 in., 11 in. x 17 in., 13 in. x 18 in., 13 in. x 19 in., 17 in. x 22 in., and other standard sizes

Custom sheet sizes by request

**Media Features** 

No Need for Cameras or Processors

High Ink Densities

• Fine-line Detail

Quick Drying Time

Heat Resistant

Dimensionally Stable

Compatible with Piezo-type, Small and Large-Format Ink Jet Printers

**Structure** 

**Recommended Handling & Storage Conditions** 

Clear Ink Jet Layer		Temperature	Relative Humidity
Clear Polyester Film	Handling	65-85°F (18-27°C)	20-60% non-condensing
Anti-Curl or Anti-static Layer	Storage	50-90°F (10-30°C)	20-80% non-condensing
	Unprinted Media	Store the unprinted media in its original plastic sleeve to protect the sheets from degradation and damage.	

**Physical Properties** 

SILKJET	SC4	UC5	WP5
Total Caliper	110μm / 4.2 mil	140μm / 5.5 mil	140μm / 5.5 mil
Basis Weight	105 g/m <sup>2</sup>	175 g/m <sup>2</sup>	175 g/m <sup>2</sup>
% Haze	4	6	6
% Gloss @ 60°	128	117	117
Shelf Life (date of manufacture)	One year	One year	One year
% Light Transmittance	93	93	93
Water Fastness	No	No	Yes
Ink Compatibility	Dye only	Dye and Pigment	Dye and Pigment
UV Density of Background	0.06	0.10	0.10
UV Density Image (E3000)	3.04	4.0	3.40
UV Density Image (E4000)	N/A	4.0	N/D
Grade	Economical	Standard	Premium
Appearance	Clear	Clear	Clear

N/D = Not Determined