

EXPOSURE UNITS CE

EXPŌS-IT High Output Florescent UV

- POWERFUL** Power vacuum hold down contours rubber neoprene rubber blanket to screen for excellent screen to film contact
- SMART** Vacuum draws through bottom manifold no holes in rubber blanket
- CONSISTENT** Electronic ballasts for quick starts & steady UV output
- ACCURATE** Digital Timer controls lights & vacuum precisely
- HIGH OUTPUT** 40 Watt H.O. bulbs 28" (71cm) long are standard
- GUARANTEED** 3 year warranty on manufacturer's defects
- SCREEN SIZE** 23" x 31" (58.4 x 78.7 cm) or 47" x 31" (119.4 x 78.7 cm) max screen O.D.
- DEPENDABLE** .25" (.63 cm) thick tempered glass, virtually eliminates breakage
- BRIGHT** High bulb density of streak-free light output, 3.63" (9.2 cm) center to center of 40W high output bulbs
- PRECISE** VRS pin registration compatible
- SPACE SAVING** E2331 fits perfectly on top of Dri-Vault 10 screen drying cabinet



E2331 \$1,950*

High output UV exposing unit w/vacuum
23" x 31" (58.4 x 78.7 cm) max screen OD
120 or 240 Volts (digital timer & legs standard)
Includes six, 28" (71cm) long x 40 watt H.O. bulbs

Options

- 240 Volt 50/60 HZ
- VRS pin registration
- Dri-Vault and E2331 combo



E4731 \$2,995*

High output UV exposing unit w/vacuum
47" x 31" (119.4 x 78.7 cm) max screen OD
120 or 240 Volts (digital timer & legs standard)
Includes twelve, 28" (71cm) long x 40 watt H.O. bulbs

Expose two 23" x 31" screens at one time!

Metal Halide Exposure Units

- FAST** 1200 Watt Instant Start Metal Halide Lamp
- EXACT** Quick & accurate exposure using Light Integrator
- CLEVER** Specially designed blanket for intimate contact with no "air strings"
- EASY** One hand operation with single bar latching system
- CAPACITY** 31" x 41" (79 x 104 cm) maximum screen OD
- GUARANTEED** 3 year warranty on manufacturer's defects
- ELECTRICAL** 120V, 60Hz, 15A, (dedicated power required)
- CONVENIENT** Light source in pull-out drawer
- EFFICIENT** Automatic vacuum draw down & release system with oil-less vacuum pump
- USER FRIENDLY** Fully automatic operation - 20 channel scroll set light integrator featuring auto-optimizer technology - Load frame, press start & walk away

Options

- 240V, 50Hz
- Light Shield Curtain

Other Sizes Available



AM-150 \$4,090*

Metal halide exposure unit, w/ vacuum,
31" x 41" (79 x 104 cm) max screen OD

*Starting List Price (USD). Price does NOT include crating and shipping charges.
6% sales tax will be added for PA billing addresses. Prices subject to change without notice.



Exposure Unit Technical Specifications




EXPOSIT model# E2331 and
DRIVault model# VDC-243410
Combo, includes wheels



Metal Halide Exposure unit AM-150

Touch Activated,
User Friendly Keypad
& LED Digital Display



20 Ch. Scroll Set Control
Light Integrator featuring
Auto-Optimize Technology



	E2331	E4731	AM-150
Overall Warranty	3 Year	3 Year	3 Year
Maximum Screen Size	23" x 31" (56 x 78.7 cm)	47" x 31" (119.4 x 78.7 cm)	31" x 41" (79 x 104 cm)
Light Source, Bulb type	Qty. (6) F28T12\BLHO, Black UV florescent 28" (71 cm) long	Qty. (12) F28T12\BLHO, Black UV florescent 28" (71 cm) long	Qty. (1) 1200W Metal Halide Lamp
Vacuum Pump, HO, Oil -less Diaphragm	1/16 HP, 24 Hg Max	(2) 1/16 HP, 24 Hg Max	1/8 HP, 25.5 Hg Max
Electrical Power	120V / 60 HZ / 3.5A - NEMA 5-15P 240V / 50/60 HZ / 2A - NEMA 6-15P Plug	120V / 60 HZ / 6.5A - NEMA 5-15P 240V / 50/60 HZ / 4A - NEMA 6-15P Plug	120V / 60 HZ / 1200W @ 15A NEMA 5-15P Plug Dedicated Power Required
Depth x Width x Height	41.6 x 36.2 x 48.3" (105.7 x 92 x 122.7 cm) Lid Dn 41.6 x 36.2 x 68.2" (105.7 x 92 x 173 cm) Lid Up	41.6 x 60.2 x 48.3" (105.7 x 153 x 122.7 cm) Lid Dn 41.6 x 60.2 x 68.2" (105.7 x 153 x 173 cm) Lid Up	45" x 52" x 45" (114 x 132 x 114 cm)
Overall Weight - Uncrated	180 lbs (81.6 kg)	N/A	300 lbs (136 kg)
Shipping Weight*	245 lbs (111 kg)	N/A	475 lbs (215.4 kg)
Shipping Dimensions*	N/A	N/A	63" x 59" x 52" (160 x 150 x 132 cm)

*All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications. Ex-works from Allentown PA.



Toll Free: 1.800.482.7839
1.800.4VASTEX