FORCED-AIR FLASH CURE UNIT

A 140 CFM blower draws air through an oversized filtered intake, sends it through an air diverter, then distributes it evenly across the entire heater face. The heat and air flow are both adjustable. Add an AutoFlash for the most versatile flash cure in the industry!



Adjustable air flow keeps skin cool in any position.

Adjustable heat shield helps maintain heater surface consistency



CE Certified	RA-18-240	RA-1824		
Price*(w/ Standard Stand)	\$1,140*	\$1,308*		
Heater Size	18" x 18" (46 x 61cm)	18" x 24" (46 x 61cm)		
Power (Wattage)	3,500w @ 240v	4,300w @ 240v		
Power Plug	NEMA 6-20P**	NEMA L6-30P** (Sold separate)		
	Features			
RELIABLE 15 Year Heater Warranty POWERFUL 3500 watt (18 x 18) or 4300 watt (18 x 24) heater VERSATILE Air only, full heat and air, or modulate air velocity and heat. Adjustable heat shield helps meintain heater surface consistency		ADJUSTABLEHeat, air speed, heat shield, height and levelEFFICIENTAir cooled outer skin and side handlesFASTFlash plastisol in as little as 4 seconds		

Options



SMART

*Starting List Price (USD). Price does NOT include crating and shipping charges.
**Domestic plugs listed. International cords available.
6% sales tax will be added for PA billing addresses. Prices subject to change without notice.

CLEAN Large filtered air intake delivers clean air to heater



Heavy duty side handles & locking casters

CONVENIENT

Flash Cure Units


CE

Technical Specifications

TUV-ISO 9001-2000 Compliant	F-100	F-1000	REDFLASH		AIR-FLASH	
Models	F-100	F-1000	R-18-240	R-1824-240	RA-18-HO	RA-1824
Heater Warranty	15 Year	15 Year	15 Year	15 Year	15 Year	15 Year
Bumper to Bumper Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year
Heater Size	16" x 16" (41 x 41 cm)	18" x 18" (46 x 46 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)
Unit Warm Up Time	15 min. (120V) or 10 min. (240V)	20 min. (120V) or 10 min (240V)	6 min.	12 min.	6–10 min	6-10 min
Heater Wattage	1625 Watt Heater	1950 Watt Heater	2600 or 3500 Watt Heater	3500 Watt Heater	3500 Watt Heater	4300 Watt Heater
Electrical Specs* / included plug (Some models require a dedicated line. 50/60 HZ for all units.)	120V/13A/1625W NEMA 5-15P 240V/6.5A/1625W NEMA 6-15-P	120V/15.6/1950W NEMA 5-20P 240V/7.8A/1950W NEMA 6-15-P	240V/9A/2600W NEMA 6-15P 240V/16A/3500W NEMA 6-20P	240V/16A/3500W/ NEMA 6-20P Plug	240V/16A/2500W NEMA 6-10P	240V/19A/4300W/ NEMA L6-30P
Electrical Specs - AutoFlash / included plug	110-125V/1A/NEMA 5-15P 220-240V/1A/NEMA 6-15P					

Shipping Weights and Dimensions

	Weight**	Dimensions**		
F-100 (Head and Stand)	39 lbs (18 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)		
F-1000 (Head and Stand)	42 lbs (19 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)		
R-18-240 (Head Only)	35 lbs (16 kg)	26" x 29" x 7" (66 x 74 x 18 cm)		
R-1824-240 (Head Only)	43 lbs (19.5 kg)	26" x 35" x 8" (66 x 90 x 20 cm)		
RA-18-HO (Head Only)	64 lbs (29 kg)	29" x 26" x 15" (74 x 66 x 38 cm)		
RA-1824 (Head Only)	74 lbs (35.5 kg)	35" x 29" x 15" (89 x 74 x 38 cm)		
AF-120/AF-240 AutoFlash kit	51 lbs (25 kg)	31" x 22" x 14" (79 x 56 x 36 cm)		
SH-STAND-WS Standard Stand for Manual Flash	22 lbs (10 kg)	37" x 7" x 3" (94 x 18 x 8 cm)		
SHHD-STAND-M Heavy Duty Stand for Manual Flash	42 lbs (19kg)	30" x 14" x 7" (76 x 35.5 x 18 cm)		
SH-LEGS-AF Standard Stand for AutoFlash	15 lbs (7 kg)	37" x 7" x 3" (94 x 18 x 8 cm)		
SHHD-STAND Heavy Duty Stand for AutoFlash	39 lbs (18 kg)	30" x 15" x 11" (76 x 38 x 28 cm)		



*If extension cord is required, consult a licensed electrician.

**All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications.



1 lb = 0.454 kg