

# INFRARED FLASH CURE REDFLASH

High wattage and coil density heater, for greater heater surface consistency.

With the Vastex cooling fan and air curtain, Vastex fashes can be set closer to the work which increases efficiency and productivity.




**NOW with digital control!**

**15 YEAR HEATER WARRANTY**



Digital percentage timer control allows for repeatable adjustments from 0-100%.



**REDFLASH**  
18" sq Shown with Standard Stand

**REDFLASH**  
18" x 24" Shown with SHHD-Stand



## RD-18-240

18" x 18" (46 x 46cm)

2,600w @ 240v

NEMA 6-15P\*\*

## RD-18-240-HO

18" x 18" (46 x 46cm)

3,500w @ 240v

NEMA 6-20P\*\*

## RD-1824-240

18" x 24" (46 x 61cm)

3,500w @ 240v

NEMA 6-20P\*\*

## Features

- RELIABLE 15 Year Heater Warranty
- POWERFUL 2600 or H.O. 3500 Watt heater (3500 standard 1824)
- USER FRIENDLY Diagnostic pilot lights & digital heat control
- CONVENIENT Heavy duty side handles & locking casters
- EFFICIENT High wattage and high heater density
- FAST Flashes plastisol in as little as 4sec
- UNIQUE Head leveler, cooling fan and air curtains.
- THIN PROFILE Ultra slim 2.75" (7 cm) height head

## Options

- Super Heavy Duty Stand
- AutoFlash
- Rotary Table

\*\* Domestic plugs listed. International cords available.















# Flash Cure Units

## Technical Specifications

<b>CE</b>	<b>F-100</b>	<b>F-1000</b>	<b>REDFLASH</b>		<b>AIR-FLASH</b>	
Models	F-100	F-1000	RD-18-240	RD-1824-240	RAD-18	RAD-1824
Heater Warranty	15 Year	15 Year	15 Year	15 Year	15 Year	15 Year
Bumper to Bumper Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year
Heater Size	16" x 16" (41 x 41 cm)	18" x 18" (46 x 46 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)
Controls	On/Off Switch	Bi-Metal control w/ adjustment knob	Digital percentage timer	Digital percentage timer	Digital percentage timer	Digital percentage timer
Unit Warm Up Time	15 min. (120V) or 10 min. (240V)	20 min. (120V) or 10 min (240V)	6 min.	12 min.	6-10 min	6-10 min
Heater Wattage	1625 Watt Heater	1950 (120V) or 2600 (240V) Watt Heater	2600 or 3500 Watt Heater	3500 Watt Heater	3500 Watt Heater	4300 Watt Heater
Electrical Specs* / included plug (Some models require a dedicated line. 50/60 HZ for all units.)	120V/13A/1625W NEMA 5-15P  240V/6.5A/1625W NEMA 6-15-P	120V/15.6/1950W NEMA 5-20P  240V/11/2600W NEMA 6-15-P	240V/11A/2600W NEMA 6-15P  240V/16A/3500W NEMA 6-20P	240V/16A/3500W/ NEMA 6-20P Plug	240V/16A/3500W NEMA 6-20P	240V/19A/4300W/ NEMA L6-30P
Electrical Specs - AutoFlash / included plug	110-125V/1A/NEMA 5-15P  220-240V/1A/NEMA 6-15P					

## Shipping Weights and Dimensions

	Weight**	Dimensions**
F-100 (Head and Stand)	39 lbs (18 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
F-1000 (Head and Stand)	42 lbs (19 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
R-18-240 (Head Only)	35 lbs (16 kg)	26" x 29" x 7" (66 x 74 x 18 cm)
R-1824-240 (Head Only)	43 lbs (19.5 kg)	26" x 35" x 8" (66 x 90 x 20 cm)
RA-18-HO (Head Only)	64 lbs (29 kg)	29" x 26" x 15" (74 x 66 x 38 cm)
RA-1824 (Head Only)	74 lbs (35.5 kg)	35" x 29" x 15" (89 x 74 x 38 cm)
AF-120/AF-240 AutoFlash kit	51 lbs (25 kg)	31" x 22" x 14" (79 x 56 x 36 cm)
SH-STAND-WS Standard Stand for Manual Flash	22 lbs (10 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND-M Heavy Duty Stand for Manual Flash	42 lbs (19kg)	30" x 14" x 7" (76 x 35.5 x 18 cm)
SH-LEGS-AF Standard Stand for AutoFlash	15 lbs (7 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND Heavy Duty Stand for AutoFlash	39 lbs (18 kg)	30" x 15" x 11" (76 x 38 x 28 cm)

NORTH AMERICAN POWER PLUG CONFIGURATION	
RECEPTACLE	PLUG
 NEMA 5-15R	 NEMA 5-15P
 NEMA 5-20R	 NEMA 5-20P
 NEMA 6-15R	 NEMA 6-15P
 NEMA 6-20R	 NEMA 6-20P
 NEMA 6-30LR	 NEMA 6-30LP

1 in = 2.54 cm  
1 lb = 0.454 kg

\*If extension cord is required, consult a licensed electrician.

\*\*All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications.

